



PROJECT	NOTES
CATALOG NO.	

Rev. 11/18/13

# LED WALL PACK

## DESCRIPTION

The DAYLIGHT TECHNOLOGY USA wall mount LED luminaire provides excellent perimeter and security lighting. Our lightweight, low footprint aluminum fixture is easy to install and brighter than any other available. This design allows for simple surface mount installations and easily replaces 70-400W HPS or Metal Halide systems.



## CHARACTERISTICS

**Optical:** 100 lm/Watt, 2700K–6000K, CRI 70 (patent pending optics)

**Electrical:** 120 –277V, 347V, or 480V @ 700 mA

**Mechanical:** Aluminum housing, 10" x 6" x 4"

**Certifications/Ratings:** CETL/CUL, ROHS, IP65 rated, DLC Listed

**Reliability:** "EncapsLED" heat sink for superior cooling and durability (patent pending)

**Warranty:** 5 years

**Options:** Dimming (D); Motion Sensor (M); Twist Lock (T)



## PERFORMANCE

Model #	System Wattage	Lumens @ 5000K	MH/HPS Equivalent
DL-WP-10W	12	1,200	70W
DL-WP-20W	22	2,200	70w-100W
DL-WP-30W	33	3,300	100W - 250W
DL-WP-40W	44	4,400	250W - 400W
DL-WP-50W	55	5,500	250W - 400W
DL-WP-60W	65	6,500	400W

USA Made



**Advantage!**<sup>®</sup>

[www.gsaadvantage.gov](http://www.gsaadvantage.gov)

## ORDERING INFO

Series	Wattage	Color	Distribution	Finish	Options	Voltage
DL-WP	10-60W	5000 - 5000K	3 - TYPE III	WHT - White BRZ - Bronze BLK - Black SLVR - Silver	N - None P - Photocell D - Dimmable	120 - 120-277V 347 - 347V 480 - 480V
Example: DL-WP-30W-5000-3-BRZ-N-120						

For ordering or technical inquiries, contact:

[Tom@LLSLight.com](mailto:Tom@LLSLight.com), 860.770.6023

